




SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 2.1 SDS Revision Date: 3/4/2018

1. PRODUCT & COMPANY IDENTIFICATION

| | | |
|-----|------------------------|--|
| 1.1 | Product Name: | PROcussionCare® WearBarrier® (NON-AEROSOL Trigger Spray) |
| 1.2 | Chemical Name: | See Section 3 Composition & Ingredient information |
| 1.3 | Item Number | #SS14304 |
| 1.4 | Trade Names: | Sound Synergies WearBarrier® (NON-AEROSOL Trigger Spray) |
| 1.5 | Product Use: | Specialty Conditioner Barrier Film Lubricant for Drumheads, Sticks & Mallets |
| 1.6 | Distributor's Name: | Multi-Marketing Corporation |
| 1.7 | Distributor's Address: | 3404 84 th Street East, Tacoma, WA 98446-2610 USA |
| 1.8 | Emergency Phone: | CHEMTREC +1 (800) 424-9300 / +1 (703) 527-3887 |
| 1.9 | Business Phone / Fax: | +1 (253) 365-3510 / +1 (800) 567-3617 |

2. HAZARDS IDENTIFICATION

| | | | |
|-----|------------------------|---|--|
| 2.1 | Hazard Identification: | <p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS. DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS. Classification: Flam. Liq. 2, Asp. Tox. 1, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, Chronic Aq. Tox. 2</p> | |
| 2.2 | Label Elements: | <p>Hazard Statements (H): H225 – Highly flammable liquid and vapor. H304 – May be fatal if swallowed and enters airways. H315 – Causes skin irritation. H319 – Causes serious eye irritation. H336 – May cause drowsiness or dizziness. H411 – Toxic to aquatic life with long lasting effects. Precautionary Statements (P): P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 – Keep container tightly closed. P240 – Ground and bond container and receiving equipment. P241 – Use explosion-proof electrical/ ventilating/ lighting equipment. P242 – Use non-sparking tools. P243 – Take action to prevent static discharges. P261 – Avoid breathing mist/vapor/spray. P264 – Wash thoroughly after handling. P271 – Use only outdoors or in a well-ventilated area. P273 – Avoid release to the environment. P280 – Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 – Do not induce vomiting. P303+P361+P353 – IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P321 – Specific treatment see section 4 of this SDS. P332+P313 – If skin irritation occurs: Get medical advice/attention. P304 – IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. P337+313 – If eye irritation persists: Get medical advice or attention. P362+P364 – Take off contaminated clothing and wash it before reuse. P370+P378 – In case of fire: use Alcohol Resistant-Foam, CO₂, or Water Jet to extinguish. P391 – Collect spillage. P403+P233+P235 – Store in a well-ventilated place. Keep container tightly closed. Keep cool. P405 – Store locked up. P501 – Dispose of contents/container to licensed treatment, storage and disposal facility (TSDF).</p> |  |
| 2.3 | Other Warnings: | <p>In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. KEEP OUT OF REACH OF CHILDREN.</p> | |

3. COMPOSITION & INGREDIENT INFORMATION

| CHEMICAL NAME(S) | CAS No. | RTECS No. | EINECS No. | % | EXPOSURE LIMITS IN AIR (mg/m ³) | | | | | | | | OTHER |
|---------------------|----------|-----------|------------|------|---|------|--------|---------|---------|------|------|------|-------|
| | | | | | ACGIH | | NOHSC | | | OSHA | | | |
| | | | | | TLV | STEL | ES-TWA | ES-STEL | ES-PEAK | PEL | STEL | IDLH | |
| HEXANE | 110-54-3 | MN9275000 | 203-777-6 | ≤ 75 | 50 | 1000 | 20 | 72 | NF | 500 | NA | 1100 | |
| PROPRIETARY MIXTURE | NA | NA | NA | ≤ 30 | NA | NA | NF | NF | NF | NA | NA | NA | |

4. FIRST AID MEASURES

| | | |
|-----|------------|---|
| 4.1 | First Aid: | <p>Ingestion: If ingested, do not induce vomiting. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.</p> <p>Eyes: Splashes are not likely; however, if product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation persists, contact a physician immediately.</p> <p>Skin: If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.</p> <p>Inhalation: Remove victim to fresh air at once. If breathing is difficult, provide supplemental oxygen. If breathing has stopped, provide artificial respiration. Seek immediate medical attention. Provide supportive treatment, keeping victim warm and quiet.</p> |
|-----|------------|---|



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards SDS Revision: 2.1 SDS Revision Date: 3/4/2018

4. FIRST AID MEASURES – cont'd

| | | | | | | | | | | | | | | | | | |
|-----------------------------|--|---|---------------|--|----------|---------------------|--|----------|-------------------------|--|----------|-----------------------------|--|----------|-------------|-------------|--------------|
| 4.2 | Effects of Exposure: | <p><u>Ingestion:</u> If product is swallowed, may cause nausea, vomiting and/or diarrhea.</p> <p><u>Eyes:</u> This product can cause transient mild eye irritation with short-term contact with liquid sprays or mists.</p> <p><u>Skin:</u> This product can cause mild, transient skin irritation with short-term exposure.</p> <p><u>Inhalation:</u> Exposure may cause respiratory tract irritation in some sensitive individuals.</p> | | | | | | | | | | | | | | | |
| 4.3 | Symptoms of Overexposure: | <p><u>Skin:</u> Prolonged contact with skin may result in irritation of skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas.</p> <p><u>Eyes:</u> Overexposure in eyes may cause redness, itching and watering (risk of serious damage to eyes). Contact may cause serious eye irritation including stinging, watering, redness.</p> <p><u>Ingestion:</u> Nausea, vomiting, severe abdominal pain.</p> <p><u>Inhalation:</u> Coughing, wheezing, swelling of throat, irritation in mucous membranes, difficulty breathing.</p> | | | | | | | | | | | | | | | |
| 4.4 | Acute Health Effects: | Moderate irritation to eyes. Moderate irritation to skin near affected areas, solvent may degrease the skin. Acute health hazards may be delayed. Most common symptoms include irritating properties to eyes, respiratory system and skin. | | | | | | | | | | | | | | | |
| 4.5 | Chronic Health Effects: | The material may accentuate any pre-existing dermatitis condition. | | | | | | | | | | | | | | | |
| 4.6 | Target Organs: | Eyes, Skin, Respiratory System | | | | | | | | | | | | | | | |
| 4.7 | Medical Conditions Aggravated by Exposure: | <p>Persons with pre-existing skin disorders, eye problems, or impaired kidney function may be more susceptible to the effects of the substance.</p> <table border="1" style="float: right;"> <tr><td colspan="2">HEALTH</td><td>2</td></tr> <tr><td colspan="2">FLAMMABILITY</td><td>3</td></tr> <tr><td colspan="2">PHYSICAL HAZARDS</td><td>0</td></tr> <tr><td colspan="2">PROTECTIVE EQUIPMENT</td><td>G</td></tr> <tr> <td>EYES</td> <td>SKIN</td> <td>LUNGS</td> </tr> </table> | HEALTH | | 2 | FLAMMABILITY | | 3 | PHYSICAL HAZARDS | | 0 | PROTECTIVE EQUIPMENT | | G | EYES | SKIN | LUNGS |
| HEALTH | | 2 | | | | | | | | | | | | | | | |
| FLAMMABILITY | | 3 | | | | | | | | | | | | | | | |
| PHYSICAL HAZARDS | | 0 | | | | | | | | | | | | | | | |
| PROTECTIVE EQUIPMENT | | G | | | | | | | | | | | | | | | |
| EYES | SKIN | LUNGS | | | | | | | | | | | | | | | |

5. FIREFIGHTING MEASURES

| | | | |
|-----|---------------------------|---|--|
| 5.1 | Fire & Explosion Hazards: | DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. Flammable Liquid Class IB. This material will release vapors when heated above the flash point temperature that can ignite when exposed to a source of ignition. In enclosed spaces, heated vapor can ignite with explosive force. Mists or sprays may burn at temperatures below the flash point. As a result of combustion exposure to such products may result in health hazards | |
| 5.2 | Extinguishing Methods: | Alcohol Resistant-Foam, CO ₂ , or Water Jet | |
| 5.3 | Firefighting Procedures: | This product is a Class IB flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. First responders should wear eye protection. Structural firefighters must wear SCBAs and full protective equipment. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. Fight fires as for surrounding materials. | |

6. ACCIDENTAL RELEASE MEASURES

| | | |
|-----|---------|---|
| 6.1 | Spills: | <p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of drains, municipal sewers and open bodies of water.</p> |
|-----|---------|---|

7. HANDLING & STORAGE INFORMATION

| | | |
|-----|---------------------------|---|
| 7.1 | Work & Hygiene Practices: | Do not eat, drink or smoke when handling this product. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water. Clean all spill promptly. |
| 7.2 | Storage & Handling: | Use and store in a cool, dry, well-ventilated area. Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Do not store in unmarked containers or storage devices. Do not store in unmarked containers or storage devices. Recommended maximum shelf life: 36 months. |
| 7.3 | Special Precautions: | Empty containers may contain product residue. Do not pressurize, cut, heat or weld empty containers. Do not reuse empty containers without commercial cleaning or reconditioning. Keep container tightly closed when not in use. Do not store at temperatures above 120 °F (49 °C). Store away from strong oxidizers. |



SAFETY DATA SHEET




Page 3 of 6
SDS-014-8T

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 2.1

SDS Revision Date: 3/4/2018

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

| 8.1 | Exposure Limits: ppm (mg/m ³) | CHEMICAL NAME(S) | ACGIH | | NOHSC | | | OSHA | | | OTHER |
|-----|--|--|-------|------|--------|---------|---------|------|------|------|---|
| | | | TLV | STEL | ES-TWA | ES-STEL | ES-PEAK | PEL | STEL | IDLH | |
| | | HEXANE | 50 | 1000 | 20 | 72 | NF | 500 | NA | 1100 | |
| 8.2 | Ventilation & Engineering Controls: | When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. | | | | | | | | | |
| 8.3 | Respiratory Protection: | No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. | | | | | | | | | |
| 8.4 | Eye Protection: | Safety glasses with side shields must be used when handling or using this product. A protective face shield is also recommended. Wear goggles and face shield if material is heated above 125°F (51°C). Have suitable eye wash water available. | | | | | | | | |  |
| 8.5 | Hand Protection: | Use gloves constructed of chemical resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. | | | | | | | | |  |
| 8.6 | Body Protection: | Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®) if splashing or spraying conditions are present. Protective clothing should include long-sleeves, apron, boots and additional facial protection. Remove contaminated clothing. Launder contaminated clothing before reusing. Contaminated leather goods should be removed promptly and discarded. When handling large quantities (e.g., ≥ 1 gallon), eye wash stations and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. | | | | | | | | |  |

9. PHYSICAL & CHEMICAL PROPERTIES

| | | |
|------|---|--|
| 9.1 | Appearance: | Pale yellow liquid. |
| 9.2 | Odor: | Characteristic odor |
| 9.3 | Odor Threshold: | NA |
| 9.4 | pH: | NA |
| 9.5 | Melting Point/Freezing Point: | - 20 °C (n-Hexane) |
| 9.6 | Initial Boiling Point/Boiling Range: | 69 °C (155 °F) @ 760 mm Hg |
| 9.7 | Flashpoint: | - 22 °C (-7.6 °F), n-Hexane |
| 9.8 | Upper/Lower Flammability Limits: | UEL 1.25 / LEL 7.0 |
| 9.9 | Vapor Pressure: | 160 mbar @ 20 °C (n-Hexane) |
| 9.10 | Vapor Density: | NA |
| 9.11 | Relative Density: | 0.675 – 0.696 |
| 9.12 | Solubility: | negligible |
| 9.13 | Partition Coefficient (log P _{ow}): | NA |
| 9.14 | Autoignition Temperature: | 223 °C (433.4 °F), n-Hexane |
| 9.15 | Decomposition Temperature: | NA |
| 9.16 | Viscosity: | 0.31 mPa @ 20 °C (n-Hexane) |
| 9.17 | Other Information: | Vapor Density (n-Hexane): 2.97 (air = 1.0); VOC Content: 120 g/L |

10. STABILITY & REACTIVITY

| | | |
|------|-----------------------------------|--|
| 10.1 | Stability: | Relatively stable under ambient conditions when stored properly. |
| 10.2 | Hazardous Decomposition Products: | If exposed to extremely high temperatures, products of thermal decomposition may include irritating vapors and toxic gases (e.g., metallic oxides, oxides of carbon & nitrogen). |
| 10.3 | Hazardous Polymerization: | Will not occur. |
| 10.4 | Conditions to Avoid: | Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame, strong oxidizers. |
| 10.5 | Incompatible Substances: | Strong oxidizers, peroxides or strong acids. |



SAFETY DATA SHEET

Page 4 of 6
SDS-014-8T

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 2.1

SDS Revision Date: 3/4/2018

11. TOXICOLOGICAL INFORMATION

| | | | | |
|------|------------------------------|---|-----------------|----------------|
| 11.1 | Routes of Entry: | Inhalation: YES | Absorption: YES | Ingestion: YES |
| 11.2 | Toxicity Data: | This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product. n-Hexane: Draize test, rabbit, eye: 10 mg Mild; Inhalation, mouse: LC ₅₀ = 150,000 mg/m ³ /2H; Inhalation, rat: LC ₅₀ = 48,000 ppm/4H; Inhalation, rat: LC ₅₀ = 627,000 mg/m ³ /3M; Oral, rat: LD ₅₀ = 25 gm/kg. Tumorigenic effects have been reported in experimental animals. | | |
| 11.3 | Acute Toxicity: | Moderate irritation to eyes and skin near affected areas. | | |
| 11.4 | Chronic Toxicity: | This material may aggravate any pre-existing skin condition (e.g., dermatitis). | | |
| 11.5 | Suspected Carcinogen: | NA | | |
| 11.6 | Reproductive Toxicity: | WARNING: This product can expose you to chemicals including Hexane, which is known to the State of California to cause reproductive harm. For more information, go to www.P65Warnings.ca.gov . | | |
| | Mutagenicity: | This product is not reported to produce mutagenic effects in humans. | | |
| | Embryotoxicity: | This product is not reported to produce embryotoxic effects in humans. | | |
| | Teratogenicity: | This product is not reported to cause teratogenic effects in humans. | | |
| | Reproductive Toxicity: | WARNING: This product can expose you to chemicals including Hexane, which is known to the State of California to cause reproductive harm. For more information, go to www.P65Warnings.ca.gov . | | |
| 11.7 | Irritancy of Product: | The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) upon prolonged or repeated exposure. | | |
| 11.8 | Biological Exposure Indices: | NE | | |
| 11.9 | Physician Recommendations: | Treat symptomatically. | | |

12. ECOLOGICAL INFORMATION












| | | |
|------|------------------------------|---|
| 12.1 | Environmental Stability: | Estimated BCF values = 2.24 and 2.89. These values suggest that hexane will show low bioconcentration in aquatic organisms. Estimated K _{oc} value = 4.11. Expected to exist entirely in the vapor phase in ambient air, expected half life 2.8 days. Expected to biodegrade but not bioconcentrate. |
| 12.2 | Effects on Plants & Animals: | This product will show slight soil mobility and is expected to rapidly volatilize from moist surface soils. Volatilization and adsorption are expected to be the most important fate processes. |
| 12.3 | Effects on Aquatic Life: | Photolysis or hydrolysis are not expected to be important. WGK (Germany): 1 |

13. DISPOSAL CONSIDERATIONS

| | | |
|------|-------------------------|---|
| 13.1 | Waste Disposal: | Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler. |
| 13.2 | Special Considerations: | U.S. EPA Hazardous Waste: D001 (Characteristic – Ignitability). If the material is unsuitable for recycling or reclamation, enclosed-controlled incineration is recommended unless otherwise prohibited by local ordinance. |

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

| | | | |
|------|----------------------|---|--|
| 14.1 | 49 CFR (GND): | UN1208, HEXANES, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) or CONSUMER COMMODITY, ORM-D, (IP VOL ≤ 1.0 L) – until 01/01/2021 |  or  |
| 14.2 | IATA (AIR): | UN1208, HEXANES, 3, II (LTD QTY, IP VOL ≤ 0.5 L) or ID8000, CONSUMER COMMODITY, 9 (IP VOL ≤ 0.5 L) |   OR   |
| 14.3 | IMDG (OCN): | UN1208, HEXANES, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) |  |
| 14.4 | TDGR (Canadian GND): | UN1208, HEXANES, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) |  |
| 14.5 | ADR/RID (EU): | UN1208, HEXANES, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) |  |
| 14.6 | SCT (MEXICO): | UN1208, HEXANOS, 3, II, (CANT. LTDA., IP VOL ≤ 1.0 L) |  |
| 14.7 | ADGR (AUS): | UN1208, HEXANES, 3, II, (LTD QTY, IP VOL ≤ 1.0 L) |  |



SAFETY DATA SHEET



Page 5 of 6
SDS-014-8T

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards




SDS Revision: 2.1

SDS Revision Date: 3/4/2018

15. REGULATORY INFORMATION

| | | |
|------|-------------------------------|---|
| 15.1 | SARA Reporting Requirements: | This product contains <u>Hexane</u> , a substance subject to SARA Title III, Section 313 reporting requirements. |
| 15.2 | SARA TPQ: | There are no specific Threshold Planning Quantities for the components of this product. |
| 15.3 | TSCA Inventory Status: | The components of this product are listed on the TSCA Inventory. |
| 15.4 | CERCLA Reportable Quantity: | <u>Hexane</u> : 2,270 kg (5,000 lbs); |
| 15.5 | Other Federal Requirements: | This material does not contain any hazardous air pollutants. None of the components in this product are listed as priority pollutants under the CWA. None of the components in this product are listed as toxic pollutants under the CWA. |
| 15.6 | Other Canadian Regulations: | This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. None of the components of this product are listed on the Priorities Substances List. Class B2, D2B (Flammable Liquid, Other Toxic Effects)  |
| 15.7 | State Regulatory Information: | <u>Hexane</u> is found on the following state criteria list: Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), Pennsylvania Right to Know (PA) and Washington Permissible Exposures List (WA). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI). |
| 15.8 | Other Requirements: |  WARNING: This product can expose you to chemicals including Hexane, which is known to the State of California to cause reproductive harm. For more information, go to www.P65Warnings.ca.gov . |

16. OTHER INFORMATION

| | | | |
|------|----------------------|---|--|
| 16.1 | Other Information: | DANGER! HIGHLY FLAMMABLE LIQUID AND VAPOR. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS. CAUSES SKIN IRRITATION. CAUSES SERIOUS EYE IRRITATION. MAY CAUSE DROWSINESS OR DIZZINESS. TOXIC TO AQUATIC LIFE WITH LONG LASTING EFFECTS. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Avoid breathing mist/vapor/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do not induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Specific treatments see section 4 of this SDS. If skin irritation occurs: Get medical advice/attention. IF INHALED: Remove person to fresh and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. In case of fire: use Alcohol Resistant-Foam, CO ₂ , or Water Jet to extinguish. Collect spillage. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. KEEP OUT OF REACH OF CHILDREN.  WARNING: This product can expose you to chemicals including Hexane, which is known to the State of California to cause reproductive harm. For more information, go to www.P65Warnings.ca.gov . | |
| 16.2 | Terms & Definitions: | See last page of this Safety Data Sheet. | |
| 16.3 | Disclaimer: | This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Multi-Marketing Corporation's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition. | |
| 16.4 | Prepared for: | Multi-Marketing Corporation 3404 84 th Street East Tacoma, WA 98446-2610 USA Tel: +1 (253) 365-3510 Fax: +1 (800) 567-3617 E-mail: tech@multimarketingco.com |  MULTI-MARKETING CORP. Boundary Film Solutions™ DynaGilde® Plus with HD4X™ |
| 16.5 | Prepared by: | ShipMate, Inc. P.O. Box 787 Sisters, Oregon 97759-0787 USA Tel: +1 (310) 370-3600 Fax: +1 (310) 370-5700 http://www.shipmate.com |  ShipMate® <i>Dangerous Goods Training & Consulting</i> |



SAFETY DATA SHEET

Page 6 of 6
SDS-014-8T

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, GHS & 1272/2008/EC Standards

SDS Revision: 2.1

SDS Revision Date: 3/4/2018

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

| | |
|------------|--|
| CAS No. | Chemical Abstract Service Number |
| RTECS No. | Registry of Toxic Effects of Chemical Substances Number |
| EINECS No. | European Inventory of Existing Commercial Chemical Substances Number |

EXPOSURE LIMITS IN AIR:

| | |
|-------|--|
| ACGIH | American Conference on Governmental Industrial Hygienists |
| IDLH | Immediately Dangerous to Life and Health |
| NOHSC | National Occupational Health and Safety Commission (Australia) |
| OSHA | U.S. Occupational Safety and Health Administration |
| PEL | Permissible Exposure Limit |
| STEL | Short Term Exposure Limit |
| TLV | Threshold Limit Value |
| TWA | Time Weighted Average |

FIRST AID MEASURES:

| | |
|-----|--|
| CPR | Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body. |
|-----|--|

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

| | |
|---|-----------------|
| 0 | Minimal Hazard |
| 1 | Slight Hazard |
| 2 | Moderate Hazard |
| 3 | Severe Hazard |
| 4 | Extreme Hazard |

| |
|----------------------------|
| HEALTH |
| FLAMMABILITY |
| PHYSICAL HAZARDS |
| PERSONAL PROTECTION |

PERSONAL PROTECTION RATINGS:

| | |
|---|--|
| A | |
| B | |
| C | |
| D | |
| E | |
| F | |

| | |
|---|--|
| G | |
| H | |
| I | |
| J | |
| K | |
| X | Consult your supervisor or SOPs for special handling directions. |

| | | | |
|----------------------|-----------------------------------|----------------------------------|---------------------------|
| | | | |
| Safety Glasses | Splash Goggles | Face Shield & Protective Eyewear | Gloves |
| | | | |
| Boots | Protective Apron | Protective Clothing & Full Suit | Dust Respirator |
| | | | |
| Full Face Respirator | Dust & Vapor Half-Mask Respirator | Full Face Respirator | Airline Hood/Mask or SCBA |

OTHER STANDARD ABBREVIATIONS:


| | |
|---------|--|
| Carc | Carcinogenic |
| Irrit | Irritant |
| NA | Not Available |
| NR | No Results |
| ND | Not Determined |
| NE | Not Established |
| NF | Not Found |
| SCBA | Self-Contained Breathing Apparatus |
| Sens | Sensitization |
| STOT RE | Specific Target Organ Toxicity – Repeat Exposure |
| STOT SE | Specific Target Organ Toxicity – Single Exposure |

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

| | |
|------------------------------------|---|
| FLAMMABILITY LIMITS IN AIR: | |
| Autoignition Temperature | Minimum temperature required to initiate combustion in air with no other source of ignition |
| LEL | Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source |
| UEL | Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source |

HAZARD RATINGS:

| | |
|---------|-----------------|
| 0 | Minimal Hazard |
| 1 | Slight Hazard |
| 2 | Moderate Hazard |
| 3 | Severe Hazard |
| 4 | Extreme Hazard |
| ACD | Acidic |
| ALK | Alkaline |
| COR | Corrosive |
| W | Use No Water |
| OX | Oxidizer |
| TREFOIL | Radioactive |



TOXICOLOGICAL INFORMATION:

| | |
|--|---|
| LD ₅₀ | Lethal Dose (solids & liquids) which kills 50% of the exposed animals |
| LC ₅₀ | Lethal concentration (gases) which kills 50% of the exposed animal |
| ppm | Concentration expressed in parts of material per million parts |
| TD ₁₀ | Lowest dose to cause a symptom |
| TCLo | Lowest concentration to cause a symptom |
| TD ₁₀ , LD ₁₀ , & LD ₀₁ or TC, TC ₀₁ , LC ₁₀ , & LC ₀₁ | Lowest dose (or concentration) to cause lethal or toxic effects |
| IARC | International Agency for Research on Cancer |
| NTP | National Toxicology Program |
| RTECS | Registry of Toxic Effects of Chemical Substances |
| BCF | Bioconcentration Factor |
| TL _m | Median threshold limit |
| log K _{OW} or log K _{OC} | Coefficient of Oil/Water Distribution |

REGULATORY INFORMATION:

| | |
|-------|--|
| WHMIS | Canadian Workplace Hazardous Material Information System |
| DOT | U.S. Department of Transportation |
| TC | Transport Canada |
| EPA | U.S. Environmental Protection Agency |
| DSL | Canadian Domestic Substance List |
| NDSL | Canadian Non-Domestic Substance List |
| PSL | Canadian Priority Substances List |
| TSCA | U.S. Toxic Substance Control Act |
| EU | European Union (European Union Directive 67/548/EEC) |
| WGK | Wassergefährdungsklassen (German Water Hazard Class) |

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

| | | | | | | | |
|------------|-----------|-----------|----------|------------|------------|-----------|----------|
| | | | | | | | |
| Class A | Class B | Class C | Class D1 | Class D2 | Class D3 | Class E | Class F |
| Compressed | Flammable | Oxidizing | Toxic | Irritation | Infectious | Corrosive | Reactive |

CLP/GHS (1272/2008/EC) PICTOGRAMS:

| | | | | | | | | |
|-----------|-----------|----------|-------------|-----------|-------|--------------------|---------------|-------------|
| | | | | | | | | |
| GHS01 | GHS02 | GHS03 | GHS04 | GHS05 | GHS06 | GHS07 | GHS08 | GHS09 |
| Explosive | Flammable | Oxidizer | Pressurized | Corrosive | Toxic | Harmful Irritating | Health Hazard | Environment |