

CGES™

Thermoplastic Exit Sign

The CGES™ Thermoplastic Exit Sign features a low-profile design ideal for commercial and institutional installations. The body is constructed of an injection-molded thermoplastic housing and solid state circuitry. The sign uses high output red or green LEDs to illuminate the “EXIT” wording. This unit comes standard with 2 faceplates, 1 backplate and a mounting canopy.



Features

Body	Injection molded Impact-resistant thermoplastic housing Snap-in canopy Field applicable arrows Universal knockout patterns
Face	Universal
Mounting	Top, end, or back mounts Canopy included
Illumination	Red or green letters, LED illumination
Battery	4.8 Volt Rechargeable NiCad battery
Operating Temp	68°F to 122°F (20°C to 50°C)
Electronics	Solid state transfer Automatic solid state charger LED AC-On status indicator
Self-Diagnostics (Option)	The Self-Diagnostic test performs monthly, biannually, and annual tests to ensure reliability. Meets electrical and life safety codes
Warranty	3 -year limited warranty

Highlights

- Consumes less than 5 Watts of electricity
- Rechargeable NiCad battery
- Simple 3 wire installation
- Damp location rated

Compliance

- ANSI/NFPA-101
- ANSI/NFPA-70
- ANSI/UL924
- ICC (IBC & IFC)
- C-UL
- OSHA



CGES™

Thermoplastic Exit Sign

Product Dimensions & Details

Weight: 3 lbs. (1.36kg)

Ordering Information



Example: CGES-EM-R-U-WH-SD

Series

CGES = CGES™ Thermoplastic Exit Sign

Operation

AC = AC Only
EM = Battery Backup

Legend

R = Red
G = Green

Face Count

U = Universal Face

Housing Color

WH = White
BK = Black

Options

SD = Self Diagnostics
RC = Remote Capable
UC = Listed for Canada
CX = Dual Circuit 120/277 V
CW = Custom Wording

Power Consumption

Power Input: 120/277 VAC

Operation	Max Watts
Battery Backup	3.8

The Exit Store LLC
303 W Lancaster Ave #138
Wayne, PA 19087
Toll Free: 844-438-3948 [844-GET-EXIT]
Tel: 484-913-1916
Fax: 484-913-1919
sales@theexitstore.com

www.theexitstore.com