



RTX550 Specs

General Dimensions and Weights		
Weight (basic tractor, rubber tires)	5600 lbs	2540.1 kg
Weight (basic tractor, tracks)	7800 lbs	3538 kg
Length (basic tractor, rubber tires)	123.5"	313.7 cm
Length (basic tractor, tracks)	129.4"	328.7 cm
Width (basic tractor, rubber tires)	72.4"	183.9 cm
Width (basic tractor, tracks)	70.5"	179.1 cm
Height (basic tractor, rubber tires)	96.8"	245.9 cm
Height (basic tractor, tracks)	98.2"	249.4 cm
Ground Clearance (rubber tires)	8.8"	22.4 cm
Ground Clearance (tracks)	10.2"	25.9 cm
Angle of approach (basic tractor, rubber tires)	20 deg	
Angle of approach (basic tractor, tracks)	26 deg	
Roll Over Protection Structure (2-post ROPS)	17000 lbs	7711.1 kg

Capacities		
Fuel Tank	27 gal	102.2 L

Hydraulic Tank	18 gal	68.1 L
Hydraulic System	20 gal	75.7 L
Coolant	3.1 gal	11.7 L

Ground Drive - Rubber Tire

Tire size	31 " x 15 " (78.74 cm x 38.1 cm)	
-----------	----------------------------------	--

Ground Drive - Tracks

Maximum forward transport speed (high)	4.1 mph	6.6 km/h
Maximum reverse transport speed (high)	4.1 mph	6.6 km/h
Track width	15"	38.1 cm
Ground pressure (basic tractor only)	3 psi	.2 bar

Axle Options

Front Axle Type	Steerable planetary	
Rear Axle Type	Steerable planetary with gearbox	
Outside turning diameter (tracks, front and rear steer)	20.1'	

Electrical System

System Voltage	12 Volt	
----------------	---------	--

ATTACHMENTS

Copyright © 2010-2015. Vermeer Corporation. All Rights Reserved.

www.vermeer.com